# DAR 112/6 5,5





### Short description

Axial duct fan, DN 1120, three-phase AC, nominal power 5.5 kW

### Application examples

Production facility, Workplace, Commercial premises, Industrial building

Article number

0073.0182

#### Technical data

Air flow volume	56.880 m³/h				
Rotating speed	960 1/min				
Impeller type	axial				
Speed controllable	✓				
Reversing capacity	-				
Type of voltage	Three-phase AC				
Rated voltage	400 V				
Frequency	50 Hz				
Nominal output	5.500 W				
I <sub>nom</sub>	12,38 A				
Degree of protection	IP 55				
Insulation class	F				
Pole-changeable	- Duct				
Installation site					
Installation position	Horizontal				
Housing material	Sheet steel with epoxy coating				
Impeller material	Polyamide				
Colour	grey 180 kg				
Weight					
Weight including packaging	205 kg				
Nominal size	1.120 mm				
Width	1.250 mm 750 mm				
Height					
Depth	1.250 mm				
Width with packaging	1.500 mm				
Height with packaging	1.150 mm				
Depth with packaging	1.490 mm				
Airstream temperature at I <sub>Max</sub>	-10 °C up to 50 °C				
PTC DIN 44082	M 100				



# DAR 112/6 5,5

Packing unit	1 piece
Range	С
GTIN (EAN)	4012799731825

# Technical data according to ErP in Best Efficiency Point (BEP)

Total efficiency η	44,9 %				
Measurement category	С				
Efficiency category	static				
Efficiency level N	46,1 no				
VSD necessary					
Year of manufacture	see rating plate				
Manufacturer's name / official registration number / manufacturer's	Maico Elektroapparate-Fabrik GmbH / Freiburg registration				
place of establishment	court, HRB 601233 / Villingen-Schwenningen 0073.0182 6,314 kW / 37.080 m³/h / 275 Pa				
Art. No.					
P <sub>BEP</sub> / Air volume <sub>BEP</sub> / P <sub>fs, BEP</sub>					
n <sub>BEP</sub>	970 1/min				
Specific ratio	≈ 1				
Information about dismantling and disposal	see mounting instructions				
Information about installation, operation and repairs	see mounting instructions				
Objects used to measure efficiency which are not described by the	-				
measurement category					
I <sub>BEP</sub>	12,38 A				
Sound power levelL <sub>WA7</sub>	93 dB(A)				

### Sound power level in octave range


	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	Total
L <sub>WA5</sub> , S5	71	78	84	86	88	86	84	75	93
(dB(A))									

L<sub>WA5</sub>= free inlet sound power level in dB.

# DAR 112/6 5,5



### Characteristic curve



# Dimensioned drawing [mm]

