DAR 140/8 5,5





Short description

Axial duct fan, DN 1400, three-phase AC, nominal power 5.5 kW

Application examples

Production facility, Workplace, Commercial premises, Industrial building

Article number

0073.0194

Technical data

Air flow volume	71.280 m³/h			
Rotating speed	720 1/min			
Impeller type	axial			
Speed controllable	✓			
Reversing capacity	-			
Type of voltage	Three-phase AC			
Rated voltage	400 V			
Frequency	50 Hz			
Nominal output	5.500 W			
I _{nom}	12,22 A			
Degree of protection	IP 55			
Insulation class	F			
Pole-changeable	-			
Installation site	Duct			
Installation position	Horizontal			
Housing material	Sheet steel with epoxy coating			
Impeller material	Polyamide			
Colour	grey			
Weight	370 kg			
Weight including packaging	397 kg			
Nominal size	1.400 mm			
Width	1.540 mm			
Height	815 mm			
Depth	1.540 mm			
Width with packaging	1.600 mm			
Height with packaging	1.500 mm			
Depth with packaging	1.770 mm			
Airstream temperature at I _{Max}	-10 °C up to 50 °C			
PTC DIN 44082	M 100			





Packing unit	1 piece
Range	С
GTIN (EAN)	4012799731948

Technical data according to ErP in Best Efficiency Point (BEP)

Total efficiency η	46,2 %				
Measurement category	С				
Efficiency category	static				
Efficiency level N	47,9				
VSD necessary	no				
Year of manufacture	see rating plate				
Manufacturer's name / official registration number / manufacturer's	Maico Elektroapparate-Fabrik GmbH / Freiburg registration				
place of establishment	court, HRB 601233 / Villingen-Schwenningen				
Art. No.	0073.0194 5,521 kW / 41.400 m³/h / 222 Pa				
P _{BEP} / Air volume _{BEP} / P _{fs, BEP}					
n _{BEP}	735 1/min				
Specific ratio	≈1				
Information about dismantling and disposal	see mounting instructions				
Information about installation, operation and repairs	see mounting instructions				
Objects used to measure efficiency which are not described by the	-				
measurement category					
I _{BEP}	12,22 A				
Sound power levelL _{WA7}	90 dB(A)				

Sound power level in octave range


	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	Total	
L _{WA5} , S5	60	70	77	82	84	84	85	79	90	
(dB(A))										

L_{WA5}= free inlet sound power level in dB.

DAR 140/8 5,5



Characteristic curve



Dimensioned drawing [mm]

