DAR 63/4 1,5





Short description

Axial duct fan, DN 630, three-phase AC, nominal power 1.5 kW

Application examples

Production facility, Workplace, Commercial premises, Industrial building

Article number

0073.0122

Technical data

Lace	1.47.400.20			
Air flow volume	17.168 m³/h			
Rotating speed	1.440 1/min			
Impeller type	axial			
Speed controllable	✓			
Reversing capacity	-			
Type of voltage	Three-phase AC			
Rated voltage	400 V			
Frequency	50 Hz			
Nominal output	1.500 W			
I _{nom}	3,54 A			
Degree of protection	IP 55			
Insulation class	F			
Pole-changeable	-			
Installation site	Duct			
Installation position	Horizontal / Vertical			
Housing material	Sheet steel with epoxy coating			
Impeller material	Polyamide			
Colour	grey			
Weight	46 kg			
Weight including packaging	51 kg			
Nominal size	630 mm			
Width	730 mm			
Height	500 mm			
Depth	730 mm			
Width with packaging	830 mm			
Height with packaging	600 mm			
Depth with packaging	830 mm			
Airstream temperature at I _{Max}	-10 °C up to 50 °C			
PTC DIN 44082	M 100			





Packing unit	1 piece
Range	С
GTIN (EAN)	4012799731221

Technical data according to ErP in Best Efficiency Point (BEP)

Total efficiency η	41,3 %				
Measurement category	C static 46,5				
Efficiency category					
Efficiency level N					
VSD necessary	no				
Year of manufacture	see rating plate				
Manufacturer's name / official registration number / manufacturer's	Maico Elektroapparate-Fabrik GmbH / Freiburg registration				
place of establishment	court, HRB 601233 / Villingen-Schwenningen				
Art. No.	0073.0122				
P _{BEP} / Air volume _{BEP} / P _{fs, BEP}	1,527 kW / 12.251 m³/h / 185,2 Pa 1.420 1/min				
n _{BEP}					
Specific ratio	≈1				
Information about dismantling and disposal	see mounting instructions				
Information about installation, operation and repairs	see mounting instructions				
Objects used to measure efficiency which are not described by the	-				
measurement category					
I _{BEP}	3,54 A				
Sound power levelL _{WA7}	85 dB(A)				

Sound power level in octave range


	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	Total	
L _{WA5} , S5	63	70	75	77	79	78	77	72	85	
(dB(A))										

L_{WA5}= free inlet sound power level in dB.

DAR 63/4 1,5



Characteristic curve



Dimensioned drawing [mm]

