## DAR 71/4 3





### Short description

Axial duct fan, DN 710, three-phase AC, nominal power 3  $\ensuremath{\text{kW}}$ 

## Application examples

Production facility, Workplace, Commercial premises, Industrial building

Article number

0073.0131

#### Technical data

Lace	05.000 20			
Air flow volume	25.920 m³/h			
Rotating speed	1.440 1/min			
Impeller type	axial			
Speed controllable	✓			
Reversing capacity	-			
Type of voltage	Three-phase AC			
Rated voltage	400 V			
Frequency	50 Hz			
Nominal output	3.000 W			
I <sub>nom</sub>	6,39 A			
Degree of protection	IP 55			
Insulation class	F			
Pole-changeable	-			
Installation site	Duct			
Installation position	Horizontal / Vertical			
Housing material	Sheet steel with epoxy coating			
Impeller material	Polyamide			
Colour	grey			
Weight	60 kg			
Weight including packaging	65 kg			
Nominal size	710 mm			
Width	810 mm			
Height	520 mm			
Depth	810 mm			
Width with packaging	830 mm			
Height with packaging	600 mm			
Depth with packaging	830 mm			
Airstream temperature at I <sub>Max</sub>	-10 °C up to 50 °C			
PTC DIN 44082	M 100			





Packing unit	1 piece
Range	C
GTIN (EAN)	4012799731313

## Technical data according to ErP in Best Efficiency Point (BEP)


Total efficiency η	42,4 %			
Measurement category	С			
Efficiency category	static			
Efficiency level N	46,1			
VSD necessary	no			
Year of manufacture	see rating plate			
Manufacturer's name / official registration number / manufacturer's	Maico Elektroapparate-Fabrik GmbH / Freiburg registration			
place of establishment	court, HRB 601233 / Villingen-Schwenningen 0073.0131			
Art. No.				
P <sub>BEP</sub> / Air volume <sub>BEP</sub> / P <sub>fs, BEP</sub>	2,564 kW / 19.048 m³/h / 205,3 Pa			
n <sub>BEP</sub>	1.440 1/min			
Specific ratio	≈1			
Information about dismantling and disposal	see mounting instructions			
Information about installation, operation and repairs	see mounting instructions			
I <sub>BEP</sub>	6,39 A			
Sound power levelL <sub>WA7</sub>	88 dB(A)			

#### Sound power level in octave range

	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	Total
L <sub>WA5</sub> , S5	67	74	79	81	82	81	80	75	88
(dB(A))									

L<sub>WA5</sub>= free inlet sound power level in dB.

#### Characteristic curve



# DAR 71/4 3



## Dimensioned drawing [mm]

